



## **Recessed Floor Box**



**LTL's floor box range are unique, stylish and robust units designed to give quick and simple solutions to raised access floor installations.**

**PO Box 44101 Lower Hutt**

**Contact: 021 444 631/021 973 297**

**Fax: 04 569 3489**

## **LTL100 FB: 3 COMPARTMENT FLOOR BOX**

LTL's 3 compartment floor boxes are flexible enough to accommodate most situations of power, data and phone needs, however LTL will investigate any special requirements.

Both dividers can be removed if needed, for other applications.

### **General Features:**

- Overall dimensions 310 x 216 mm
  - Option of 3 Depths: 65, 75, and 85 mm
- Panel cut out 300 x 200mm approx.
- Reversible lid/trim assembly
- Manufactured from flame retardant ABS
- 2 cable exit flaps providing 60 x 15mm openings
- Integral moulded lifting handle
- 4 unique relocatable spring fixing clips for quick fit



## **Lid Tray Assembly**

The carpet trim and lid tray are moulded from flame retardant ABS, with both having a steel reinforced section to ensure maximum rigidity. Each lid is provided with two cable outlet brackets that are securely fixed into the lid tray, together with a moulded integral lid handle.

The carpet trim and lid tray can be rotated through 180° to allow the lid to be opened in either direction.

The standard colour of the moulding is dark grey.

### **Mounting Frame**

The mounting frame is manufactured from galvanised steel and is suitable for mounting into a 300 x 200mm approx hole cut into any access floor panel. The frame is provided with four spring clips which firmly anchor the frame into the floor panel.

### **Box Base**

The box base is manufactured from galvanised steel and is provided with 20 and 25mm knockouts on all four sides. Dividing fillets are provided to separate the internal services.

To ensure maximum security for the electrical services, the accessory plate fixing screws are located in an inaccessible position.

### **LTL50 FB: SINGLE COMPARTMENT FLOOR BOX**

LTL's single compartment floor boxes are suitable to accommodate a PDL 695 or a PDL 694 single switch socket and PDL 619MD Dataplus module.

#### **General Features:**

- Overall dimensions 216 x 112 mm
  - Option of 3 Depths: 65, 75, and 85 mm
- Panel cut out 220 x 116 mm approx.
- Stainless steel Deluxe lid assembly
- Manufactured from flame retardant ABS
- 2 cable exit flaps providing 60 x 15mm openings
- Integral moulded lifting handle
- 4 unique relocatable spring fixing clips for quick fit



### **LTL50 FBO: SINGLE COMPARTMENT OVAL FLOOR BOX**

LTL's single compartment floor boxes are suitable to accommodate a PDL 695 or a PDL 694 single switch socket and PDL 619MD Dataplus module.

#### **General Features:**

- Overall maximum dimensions 200 x 140
  - Option of 3 Depths: 65, 75, and 85 mm
- Durable plastic lid
- Manufactured from flame retardant ABS
- 2 cable exit flaps providing
- Lifting and locking handles
- 4 unique relocatable spring fixing clips for quick fit



## FLOOR BOXES & COMPONENTS

Code	Description
<b>LTL 100 FB</b>	Recessed Floor Box 310x216 and 3 depths: 65, 75 and 85 mm c/w Deluxe lid
<b>LTL 50 FB</b>	Recessed Floor Box 216x112 and 3 depths: 65, 75 and 85 mm c/w s/s Deluxe lid
<b>LTL 50 FBO</b>	Oval Floor Box 200x140x and 3 depths: 65, 75 and 85 mm c/w plastic lid
<b>LTL 695 FB</b>	Floor Box Outlet panel for PDL 695 socket or other equivalents
<b>LTL 699 FB</b>	Floor Box Outlet panel for PDL 699 socket or other equivalents
<b>LTL 619 FB</b>	Floor Box Outlet panel for 6 x Keystone adaptor clips



The LTL 100 FB accommodates any combination of three Outlet panels.

For more information please Contact Geoff Campbell or Dimitrios Gaitanos on  
021 444 631 or 021 973 297